The JetTrac[™] Family of Products

Providing instant safety for large areas.









JetTrac Shuttle*

- Stores and transports up to three JetTrac Satellite or Receiver posts for an instant barrier of up to 260 feet long!
- Shuttle carts quickly link together to form an easily pulled "train".
- Convenient storage even in tight places.
- One person can quickly deploy a large-area barrier where most needed.

JetTrac Satellite Post*

- Instantly add an additional 65' coverage into your safety zone.
- Works seamlessly with all of our JetTrac products.
- Heavy base for added stability.
- Conveniently stores and transports in our JetTrac Shuttle.

JetTrac Receiver Post*

- Instantly add a belt receiver into your safety zone.
- Works seamlessly with all of our JetTrac products.
- Heavy base for added stability.
- Conveniently stores and transports in our JetTrac Shuttle.

JetTrac Dual*

- An instant barrier, with two belts that extend up to 65' for a total of 130 linear feet. Clearly defines safe zones for large areas!
- Swiveling belt mechanisms allow for belts to extend in any direction, minimizing belt abrasion.
- Belts are weather-resistant, anti-static.
- Tubing is available in choice of Red or Black.
- Optional reflective saftey tape to provide increased visibility in low-light conditions.

JetTrac Wall-Mount*

- Create a convenient, always available barrier over an extended area with our swiveling wall-mount.
- Extends up to 65 feet!
- As with all JetTrac products, belts are weather-resistant and anti-static.



The JetTrac™ Family of Products

Providing instant safety for large areas.











Weight 48 lbs. 50 lbs. 42 lbs. 110 lbs. 9 lbs. Finish Wrinkle Black-Post (WB) Wrinkle Black (WB) Wrinkle Black (WB) Wrinkle Black (WB) Yellow (Y), Red (RID), Black (BK) Black (BK) Post Diameter 2 ¾ inches 2 ¾ inches 5 inches N/A Casing Diameter 6 ¾ inches 6 ¾ inches N/A 6 ¾ inches 6 ¾ inches 6 ¾ inches Construction Plastic Base, Steel Post, Aluminum Belt Casing Aluminum Belt Casing Base Diameter 32" x 41" 14 inches 14 inches 23" x 20" N/A Base Cover N/A Metal Metal Plastic N/A Rubberized Base N/A Standard Standard N/A N/A Belt Color Options Safety Yellow (FY), Black (BK) Standard (B), S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) Standard Standard N/A Standard Standard N/A Standard (B), S-hook (S), J-Hook (J) Schook (S), J-Hook (J) Fits Into Shuttle Includes Roll Bar Rubber Wheels Fits Into Shuttle Includes Roll Bar Rubber Wheels	J-1100K	50-5520 [*]	50-5510 [*]	50-3055	50-5500 *	50-5550 [*]
Weight 48 lbs. 50 lbs. 42 lbs. 110 lbs. 9 lbs. Finish Wrinkle Black-Post (WB) Wrinkle Black (WB) Wrinkle Black (WB) Wrinkle Black (WB) Yellow (Y), Red (RID), Black (BK) Black (BK) Post Diameter 2 ¾ inches 2 ¾ inches 5 inches N/A Casing Diameter 6 ¾ inches 6 ¾ inches N/A 6 ¾ inches 6 ¾ inches 6 ¾ inches Construction Plastic Base, Steel Post, Aluminum Belt Casing Aluminum Belt Casing Base Diameter 32" x 41" 14 inches 14 inches 23" x 20" N/A Base Cover N/A Metal Metal Plastic N/A Rubberized Base N/A Standard Standard N/A N/A Belt Color Options Safety Yellow (FY), Black (BK) Standard (B), S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) Standard Standard N/A Standard Standard N/A Standard (B), S-hook (S), J-Hook (J) Schook (S), J-Hook (J) Fits Into Shuttle Includes Roll Bar Rubber Wheels Fits Into Shuttle Includes Roll Bar Rubber Wheels		JETTRAC™ SHUTTLE*			JETTRAC™ DUAL*	
Finish Wrinkle Black-Post (WB) Wrinkle Black (WB) Wrinkle Black (WB) Yellow (Y), Red (RD), Black (BK) Satin Aluminum (SA), Black (BK) Post Diameter 2 ¾ inches 2 ¾ inches 5 inches N/A Casing Diameter 6 ¾ inches 6 ¾ inches 6 ¾ inches N/A 6 ¾ inches 6 ¾ inches Construction Plastic Base, Steel Post, Aluminum Belt Casing N/A Base Diameter 32" x 41" 14 inches 14 inches 23" x 20" N/A Rubberized Base N/A Standard Standard N/A N/A Belt Color Options Safety Yellow (FY), Black (BK) S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S) Belt Length 65 feet 65 feet N/A 65 feet 1cludes Rubber Wheels Fits Into Shuttle Fits Into Shuttle Includes Roll Bar Rubber Wheels	Height	41½ inches	40 inches	40 inches	41 inches	8 inches
Post Diameter 2 % inches 2 % inches 2 % inches 2 % inches 5 inches N/A 6 % inches 6 % inches 6 % inches 6 % inches N/A 6 % inches 6 % inches 6 % inches Construction Materials Plastic Base, Steel Post, Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum Belt Casing Aluminum N/A Metal Metal Plastic Base, Steel Post, Aluminum Belt Casing N/A N/A Standard N/A N/A Standard N/A Standard N/A N/A Belt Color Options Safety Yellow (FY), Black (BK) Standard (B), S-hook (S), J-Hook (J) Standard N/A Standard N/A Standard Standard N/A Standard Standard N/A Standard Standard Standard N/A Standard Standard Standard N/A Standard	Weight	48 lbs.	50 lbs.	42 lbs.	110 lbs.	9 lbs.
Casing Diameter 6 ¾ inches 6 ¾ inches 6 ¾ inches N/A 6 ¾ inches 6 ¾ inches 6 ¾ inches Construction Materials Plastic Base, Steel Post, Aluminum Belt Casing Aluminum Belt Casing Base Diameter 32" x 41" 14 inches 14 inches 14 inches 23" x 20" N/A Base Cover N/A N/A N/A Rubberized Base N/A Standard Standard Standard N/A Belt Color Options Safety Yellow (FY), Black (BK) Belt End Options Standard (B), S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) Standard Standard N/A Standard N/A Standard Standard N/A Standard (B), S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S) S-hook (Finish	Wrinkle Black-Post (WB)	Wrinkle Black (WB)	Wrinkle Black (WB)	(// (//	\ \ /'
Construction Plastic Base, Steel Post, Aluminum Belt Casing Steel Post, Aluminum Belt Casing Base Diameter 32" x 41" 14 inches 14 inches 23" x 20" N/A Base Diameter N/A Metal Metal Plastic N/A N/A Standard N/A N/A Rubberized Base N/A Standard Standard N/A N/A Safety Yellow (FY), Black (BK) Black (BK) S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) Standard N/A Standard Belt Standard Belt Standard Belt Standard Standard Belt Standard Standard Belt Belt Belt Belt Belt Belt Belt Belt	Post Diameter	2 ¾ inches	2 ¾ inches	2 ¾ inches	5 inches	N/A
Materials Aluminum Belt Casing N/A N/A Base Cover N/A Standard N/A Stafety Yellow (FY), Black (BK) N/A Standard (B), Safety Yellow (FY), Black (BK)	Casing Diameter	6 ¾ inches	6 ¾ inches	N/A	6 ¾ inches	6 ¾ inches
Base Cover N/A Metal Metal Metal Plastic N/A N/A N/A N/A N/A Safety Yellow (FY), Black (BK) Belt Color Options Standard (B), S-hook (S), J-Hook (J) Selt Length 65 feet Standard Standard N/A Metal Metal Plastic N/A N/A N/A N/A Safety Yellow (FY), Black (BK) N/A Safety Yellow (FY), Black (BK) N/A Standard (B), S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) S-hook (S)	Construction Materials			Steel		Aluminum
Rubberized Base N/A Standard Standard Standard N/A N/A N/A Safety Yellow (FY), Black (BK) Belt Color Options Safety Yellow (FY), Black (BK) Standard (B), S-hook (S), J-Hook (J) Standard (B), S-hook (S), J-Hook (J) Selt Length 65 feet Standard Standard N/A Standard (B), S-hook (S), J-Hook (J) Selt Length Standard N/A Standard Standard Standard N/A Standard Standard Standard N/A Standard Standard Standard Standard Standard N/A Standard	Base Diameter	32" x 41"	14 inches	14 inches	23" x 20"	N/A
Belt Color Options Safety Yellow (FY), Black (BK) Standard (B), S-hook (S), J-Hook (J) Selt Length 65 feet Slow Retracting Belt Locking Rubber Wheels Safety Yellow (FY), Black (BK) N/A Safety Yellow (FY), Black (BK) N/A Standard (B), S-hook (S), J-Hook (J) Standard (B), S-hook (S), J-Hook (J) Standard (B), S-hook (S), J-Hook (J) S-hook (S), J-Hook (J) Standard (B), S-hook (S), J-Hook (J) S-hook (S) S-hook	Base Cover	N/A	Metal	Metal	Plastic	N/A
Belt Color Options Black (BK) Black (BK)	Rubberized Base	N/A	Standard	Standard	N/A	N/A
S-hook (S), J-Hook (J) S-hook (S) S-hook (S), J-Hook (J) S-hook (S) S-hook	Belt Color Options	, ,,,	, ,,	N/A		, ,,,
Slow Retracting Belt Standard Standard N/A Standard Standard Other Locking Rubber Wheels Fits Into Shuttle Fits Into Shuttle Includes Roll Bar Rubber Wheels	Belt End Options			N/A		
Other Locking Rubber Wheels Fits Into Shuttle Fits Into Shuttle Includes Roll Bar Rubber Wheels	Belt Length	65 feet	65 feet	N/A	65 feet	65 feet
Uther Locking Rubber Wheels Fits Into Shuttle Fits Into Shuttle Rubber Wheels	Slow Retracting Belt	Standard	Standard	N/A	Standard	Standard
Extended Warranty Required Required Optional Required Required	Other	Locking Rubber Wheels	Fits Into Shuttle	Fits Into Shuttle		
	Extended Warranty	Required	Required	Optional	Required	Required

*SPECIAL NOTE: Service Contract required with purchase of each product.







